


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>A61B 7/04</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/30634</b> <b>(43) International Publication Date:</b> 28 August 1997 (28.08.97)
<b>(21) International Application Number:</b> PCT/US97/02630 <b>(22) International Filing Date:</b> 21 February 1997 (21.02.97) <b>(30) Priority Data:</b> 60/012,168      23 February 1996 (23.02.96)      US <b>(71) Applicant:</b> UNIVERSITY RESEARCH ENGINEERS AND ASSOCIATES, INC. [US/US]; 10-5 Oak Ridge Drive, Maynard, MA 01754-0676 (US). <b>(72) Inventor:</b> CALLAHAN, Thomas, F.; 10-5 Oak Ridge Drive, Maynard, MA 01754-0676 (US). <b>(74) Agent:</b> WATTS, Lynn, Fiorito; 2914 Hatboro Place, Upper Marlboro, MD 20774 (US).		<b>(81) Designated States:</b> AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

**(54) Title:** IN-EAR-CANAL AUDIO RECEIVER AND STETHOSCOPE HAVING THE SAME**(57) Abstract**

The present invention provides an in-ear-canal audio receiver (42) comprising an in-ear-canal adapter body (96) having a tapered ear plug portion (98) that is inserted into the user's ear canal. The adapter body (96) further has an opening (104) in the plug portion, an exterior annular indent (128), and an inner chamber (94) coupled to the opening of the plug portion. The inner chamber of the in-ear-canal adapter body holds a transducer assembly (92) comprising a transducer housing (54) and a transducer or speaker (56). The transducer (56) is positioned in a passage extending through the transducer housing. A torus-shaped cushion (106) is positioned in the annular indent of the in-ear-canal adapter body (96). The cushion provides comfort and establishes a good seal with the user's ear.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic			SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

**TITLE OF THE INVENTION:****IN-EAR-CANAL AUDIO RECEIVER AND STETHOSCOPE HAVING THE SAME****CROSS-REFERENCE:**

This application claims the benefit of U.S. Provisional Application No. 60/012,168 filed February 23, 1996.

**BACKGROUND OF THE INVENTION:**

The present invention was made with U.S. Government support, and the U.S. Government has certain rights in the invention.

The present invention relates to an improved audio receiver which fits in the ear canal of a user's ear and which may be used in conjunction with an electronic stethoscope or other listening device such as a headset or similar device. The present invention may also be used with a typical, mechanical stethoscope or may be used as an ambient noise reducing ear plug.

Typical, mechanical stethoscopes comprise a stethoscope head and a pair of ear tubes that are coupled to the stethoscope head and biased together by a spring mechanism. Ear pieces or tips are mounted to the ends of the ear tubes for insertion into the user's ears. A column of air in the ear tubes transmits sounds detected by the stethoscope head to the ear pieces. The spring mechanism helps hold the ear pieces positioned in the user's ears. An electronic stethoscope may also have a speaker or other electronic device in or next to the ear piece to assist in listening.

How the earpiece fits in the user's ear can effect both the comfort of the user and the overall effectiveness of the earpiece, *i.e.*, the ability of the user to hear the sounds broadcast by the earpiece. FIG. 1 illustrates various parts of a human ear 10 and particularly show the complex shape of the outer ear. The external or outer ear includes: the helix 12, a curved fold forming most of the rim of the external ear; the antihelix ridge 14, the inward curving ridge of the auricle (projecting outer portion) of the external ear; the triangular fossa or depression 16 between the antihelix 14 and the helix 12; the concha region 18, the larger depression near the opening into the ear canal; the ear lobe 20, the soft, pendulous, lower part of the external ear; the tragus 22, the fleshy prominence at the front of the external opening of the ear; the antitragus 24, the fleshy prominence opposite the tragus 22; the iscusua or notch 26 between the tragus 22 and antitragus 24; and the rim of or entrance 28 to the ear canal 30. The ear canal 30 provides

a passageway between the external ear and the tympanic membrane or ear drum 32. Part of the jaw line interface 34 is shown extending downward from the ear 10.

It is generally desirable for the ear pieces to be biased or pressed against the user's ear so that a substantially airtight seal is formed. A good seal may prevent a significant amount of the ambient sounds or noise from reaching the user's ear canal through the entrance 28 to the ear canal and interfering with the stethoscope sounds. Achieving such an airtight seal, however, can be difficult and cause considerable discomfort to the user due to the relative hardness and shape of the ear pieces.

Typical earpieces for stethoscopes have a generally ball-like configuration that does not conform to the complex shape of the human ear. In addition, the earpieces are often made from a relatively hard plastic material. When the earpiece is placed in the user's ear, it contacts and applies a force against a small area around the rim of or entrance 28 to the ear canal 30. The entrance 28 to the ear canal 30, however, can be particularly sensitive to pressure. The combination of a small contact area and the spring force from the spring mechanism of the ear tubes, therefore, oftentimes causes pain and discomfort to the user after a relatively short period of time. Furthermore, due to their bulbous configuration, the typical earpieces do not generally form a good seal with the ear and, therefore, do not serve well to reduce the amount of noise entering the user's ear canal 30 through the entrance 28.

The present invention, therefore, provides an improved ear piece which is both comfortable and creates a good seal. Furthermore, the present invention provides an ear piece which safely houses a speaker which is directed into the user's ear canal

#### **SUMMARY OF THE INVENTION:**

The present invention provides an in-ear-canal audio receiver comprising an in-ear-canal adapter body having a tapered ear plug portion that is inserted into the user's ear canal. The adapter body further has an opening in the plug portion, an exterior annular indent, and an inner chamber coupled to the opening of the plug portion. The inner chamber of the in-ear-canal adapter body holds a transducer assembly comprising a transducer housing and a transducer or speaker. The transducer is positioned in a passage extending through the transducer housing. A concha cushion is positioned on the plug portion of the in-ear-canal adapter body in the annular indent. The cushion provides comfort and establishes a good seal with the user's ear.

The cushion can also be custom configured to match the complex shape (concha and ear canal region) of the user's outer ear. The custom shape provides both greater comfort and a better seal.

The transducer assembly further comprises a transducer adapter body having a through hole and an end cap which covers one end of the through hole. The transducer fits into the through hole of the transducer adapter body, and the transducer adapter body together with the transducer are received in the passage of the transducer housing. In another embodiment of the invention, transducer is encapsulated in an encapsulating material such as an epoxy compound.

The present invention also provides a stethoscope equipped with an in-ear-canal receiver as described above. The present invention also provides an ear plug having a concha cushion.

#### **BRIEF DESCRIPTION OF THE DRAWINGS:**

The above and other objects and advantages of the invention will become apparent from consideration of the following detailed description when read in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

FIG. 1 is a side view of a human ear illustrating the various parts of the ear;

FIG. 2 is a perspective view of an electronic stethoscope equipped with an in-ear-canal audio receiver (herein "IECR") in accordance with the present invention;

FIG. 3 is a side cross-sectional view of the IECR positioned in a human ear;

FIG. 4 is an exploded side view of the IECR of FIG. 3;

FIG. 5 is a partial, side cross-sectional view of an earpiece assembly comprising the in-ear-canal ("IEC") adapter and the ear cushion, which form a part of the IECR of FIG. 3;

FIG. 6A is an end view of an ear cushion forming a portion of the IECR of FIG. 3;

FIG. 6B is a side view of the ear cushion of FIG. 6A;

FIG. 6C is a side cross-sectional view of the ear cushion of FIG. 6A;

FIG. 7 is a side view of an in-ear-canal ("IEC") adapter forming a portion of the IECR of FIG. 3;

FIG. 8A is another side view of the IEC adapter illustrating the interior contour;

FIG. 8B is an end view of the IEC adapter of FIG. 6A;

FIG. 9A is a side cross-sectional view of an end cap for a transducer adapter body (shown in FIG. 10);

FIG. 9B is an end view of the end cap of FIG. 19A;

FIG. 10 is a side cross-sectional view of an encapsulated transducer assembly comprising the end cap and a transducer positioned in a transducer adapter body, which form a part of the IECR of FIG. 3;

FIG. 11A is a side cross-sectional view of the transducer positioned in the transducer adapter body of FIG. 10;

FIG. 11B is an end view of the transducer positioned in the transducer adapter body of FIG. 11A; and

FIG. 11C is an opposing end view of the transducer positioned in the transducer adapter body of FIG. 11A;

FIG. 11D is a cross-sectional plan view of the transducer positioned in the transducer adapter body of FIG. 11A;

FIG. 12A is an exploded, side cross-sectional view of another embodiment of an encapsulated transducer assembly and transducer housing;

FIG. 12B is a side cross-sectional view of the encapsulated transducer assembly of FIG. 12B partially inserted into the transducer housing;

FIG. 12C is a side cross-sectional view of the encapsulated transducer assembly of FIG. 12A fully inserted in the transducer housing and the transducer housing mounted to the end of a stethoscope ear tube;

FIG. 13 is a side cross-sectional view of another embodiment of an IECR positioned in a human ear;

FIG. 14 is an exploded side view of the IECR of FIG. 13;

FIG. 15 is an exploded side cross-sectional view of the IECR of FIG. 13;

FIG. 16A is a front end view of a contoured ear cushion forming a portion of the IECR of FIG. 13;

FIG. 16B is side cross-sectional view of the contoured ear cushion taken along section A--A of FIG. 16A;

FIG. 16C is a side view of the contoured ear cushion of FIG. 16A;

FIG. 16D is a rear end view of the contoured ear cushion of FIG. 16A;

FIG. 17A is a side view of an IEC adapter forming a portion of the IECR of FIG. 13;

FIG. 17B is front end view of the IEC adapter of FIG. 17A;

FIG. 17C is rear end view of the IEC adapter of FIG. 17A;

FIG. 17D is cross-sectional view taken along line B--B of FIG. 17A;

FIG. 17E is cross-sectional view taken along line C--C of FIG. 17A;

FIG. 17F is cross-sectional view taken along line D--D of FIG. 17A;

FIG. 18 is an exploded side view of another embodiment of an IECR that may be used with a traditional, mechanical stethoscope;

FIG. 19 is an exploded side view of another embodiment of an IECR similar to the IECR of FIG. 18 but with a different mounting configuration; and

FIG. 20 is an exploded side view of another embodiment of an IECR that may be used with a traditional, mechanical stethoscope.

The terms "upward", "downward", "top", and "bottom" may appear in the following description for convenience in describing the invention. The use of these or like terms are not intended to limit the orientation of the invention.

#### **DETAILED DESCRIPTION OF THE INVENTION:**

The present invention provides an in-ear-canal audio receiver (hereinafter referred to as an "IECR") that may be used with an electronic stethoscope, or other electronic listening device such as a headset, for receiving sound signals and broadcasting sounds into the ear canal of a user. The IECR of the present invention is designed to comfortably fit in the user's ear and yet provide a good seal. As discussed further below, the IECR may also be used with a more conventional, mechanical stethoscope which uses a column of air in the ear tube to transmit sounds to the IECR. Or, the IECR may be used as a comfortable ear plug for passively reducing the amount ambient noise reaching the inside of a user's ear.

An example of an electronic stethoscope is described in U.S. Patent No. 5,467,775, issued November 21, 1995 to Thomas F. Callahan and Matthew G. Callahan, which is incorporated herein by reference. FIG. 2 illustrates the electronic stethoscope 40 of the '775 patent provided with two IECRs 42 in accordance with the present invention. The electronic stethoscope 40 includes two transducers (not shown) housed in a stethoscope head 44 for detecting body sounds of a patient. The sound signals are transmitted by conductors housed in

a cable 46 to a digital signal processor (not shown) carried in a pack 48 or similar container or box. The digital signal processor processes the sound signals, and conductors, housed in a pair of calipers, or ear tubes 50, carry the processed sound signals to the IECRs 42 mounted to the ends of the ear tubes 50. The IECRs 42 then broadcast the sounds to the user's inner ear. A spring mechanism 52 biases the calipers 50 together in order to hold the IECRs 42 more  
5 securely in the user's ears.

FIG. 3 illustrates a first embodiment of an in-ear-canal receiver ("IECR") 42 positioned so that a portion of the IECR projects into the ear canal 30 of a human ear 10. With reference to FIGS. 3 and 4, the IECR 42 comprises a transducer housing 54 which holds a transducer 56 and which may be attached directly to the end 58 of a stethoscope ear tube 50. The transducer  
10 housing 54 has openings 60, 62 on either end which open into first and second chambers 64, 66, respectively. The first chamber 64 is adapted to be mounted to the end 58 of the stethoscope ear tube 50 which is typically hollow and made from a metallic material along a distal section 68 (shown in FIG. 4). The first chamber 64 includes a subchamber 70 provided with threads 72 for engaging threads 74 provided on the end 58 of the stethoscope ear tube 50.

15 The configuration of the first chamber 64, however, may be modified to adapt to different terminal configurations of the stethoscope ear tube 50. For example, the end of the stethoscope ear tube may be provided with annular ridges that are press fit into corresponding annular indents provided inside the earpiece. FIG. 19, discussed in more detail further below, illustrates such a mounting arrangement between the housing and the end of the stethoscope.

20 The second chamber 66 of the transducer housing 54 is adapted to receive an encapsulated transducer assembly 76 that encloses the transducer 56. The encapsulated transducer assembly 76 comprises: a transducer adapter body 78, having a through hole 80 for receiving the transducer 56; an end cap 82, having a central through hole 84, for assisting in holding the transducer 56 within the transducer adapter body 78; the transducer 56; and a pair  
25 of conductor wires or leads 86 (shown in FIG. 4). The end cap 82 may be connected to the transducer 56 and the transducer adapter body 78 by an adhesive such as acrylic cement. The conductor wires 86 are preferably hard wired or soldered to contact points 88 provided at one end of the transducer 56 and are fed through the hollow ear tube 50 to the electronics pack 48. A passageway 90 connects the two chambers 64, 66 of the transducer housing 54 to allow  
30 passage of the electrical conductors 86 between the transducer 56 and the ear tube 50.



The entire transducer assembly 92 (*i.e.*, transducer housing 54 and encapsulated transducer assembly 76) fits into a relatively large, open-ended, chamber 94 of an in-ear-canal adapter 96 (herein "IEC adapter"). The transducer assembly 92 may be held in place by an adhesive such as acrylic cement. Alternatively, the transducer assembly 92 may be press fit into the IEC adapter chamber 94 so that the IEC adapter 96 and transducer assembly 92 may be easily separated for replacement or repair. The IEC adapter 96 has a tapered plug section 98 that is inserted into the user's ear canal 30 and a larger adapter section 100 that holds the transducer assembly 92. The chamber 94 is shown in the adapter section 100, and a circular passageway 102 that extends through the plug section 98 connects the chamber 94 to an opening 104 in the plug section 98.

A toriod cushion 106 encircles the plug section 98 of the IEC adapter 96. The IEC adapter 96 and torus-shaped cushion 106 together form an earpiece assembly 108 (FIG. 5) which is inserted into the user's ear 10. In addition to providing comfort, the torus-shaped cushion 106 forms a good seal with the concha and ear canal region (18, 28) when the IEC adapter 96 is inserted into the ear 10. Due to the spring-biasing of the stethoscope calipers 50, the IECR 42 is urged toward and into the user's ear canal 30 as shown in FIG. 3. As the IECR 42 is urged into the ear canal 30, the toriod cushion 106 is compressed against the concha and entrance (18, 28) to the ear canal 30 forming a seal. The plug section 98 of the IEC adapter 96 is urged into the ear canal 30 and also forms a good seal with the concha/ear canal 30 (18, 28).

When the IECR 42 is so positioned in the ear 10, the audio output 110 of the transducer 56 is directed into the ear canal. Depending upon the size of the transducer 56 and the encapsulated transducer assembly 76, however, the encapsulated transducer assembly 76 may be fit into the plug section 98 of the IEC adapter 96 instead of the adapter section 100. In other words, a chamber may be formed in the plug section 98 for receiving the encapsulated transducer assembly 76. In that way the transducer 56 may be brought even closer to the ear drum 32 when the IECR is positioned in the user's ear 10.

FIGS. 5, 6A-C, 7, 8A, 8B, 9A, 9B, 10, and 11A-D illustrate in detail the configurations of the components of the IECR 42. Although the following detailed discussion of the components mentions particular dimensions, the dimensions may be modified depending upon such variables as the transducer size and size of the intended user's ear. For example, where the user's ear is relatively small or large, the cushion 106 can be made correspondingly smaller or

larger, and where the transducer is relatively small or large, the encapsulating assembly 76, transducer housing 54, and IEC adapter 96 can be made correspondingly smaller or larger.

FIG. 5 partially shows the earpiece assembly 108 (IEC adapter 96 and toriod ear cushion 106) fully assembled with the torus-shaped cushion 106 positioned on the plug section 98 of the IEC adapter 96. As shown in FIGS. 6A-C, the torus-shaped cushion 106 has a circular or "donut" shape with a generally flattened, elliptical cross-section (FIG. 6C). In the embodiment illustrated, the toriod ear cushion 106 has inner and outer diameters of 0.429 inches ("in.") (1.09 centimeters ("cm")) and 0.6875 in. (1.746 cm.), respectively, and is 0.130 in. (0.33 cm.) thick. The cushion 106, however, can be larger to provide an even greater contact area between the cushion 106 and the user's ear 10, as discussed further below.

The ear cushion may also be custom configured to match the complex shape (concha and ear canal region(18, 28)) of the user's outer ear. For example, the cushion may be larger and more flattened on the side which presses against the user's ear in the concha region to provide a greater area of contact between the cushion and the user's ear. The custom shape provides both greater comfort and a better seal. FIGS. 13, and 16A-D, discussed further below, illustrate an ear cushion that is more custom configured to conform to the shape of the user's ear.

The ear cushion 106 may be made from a foam elastomer with a softness approximately in the range of 30-35 Shore A Durometer. Alternatively, the cushion 106 may comprise a highly flexible sheath filled with silicon gel or another soft material such as a moldable putty. The flexible sheath may comprise a wear resistant thin, film-like material, such as polyvinyl chloride (PVC), polyvinyl chloride-acetate, polyurethane, or kid skin leather, and be filled with a silicon gel, gel mixture or moldable putty, *e.g.*, a high viscosity silicon liquid (or gel) that is highly filled with clay (commonly known as SILLY PUTTY™) or an admixture of clay and glass microspheres. In general, the moldable material can be compounded so that it will retain its amorphous qualities and take the shape of the concha cavity in which it is compressed. Such material tends to gradually flow under pressure and body heat. Other materials can be compounded to take a permanent set so that once deformed to the shape of the user's concha, the cushion 106 will tend to retain its shape after prolonged exposure to body heat. An example of such a material is polyurethane foam. The cushion 106 may also comprise of silicone rubber or another very soft castable material.

In any case, the cushion 106 preferably comprises material that allows the cushion 106 to easily compress and conform to the shape of the concha and entrance to the ear canal region (18, 28) when the IECR 42 is pressed into the user's ear 10. The cushion 106 thus provides a comfortable interface between the spring-loaded ear tubes 50 and the concha region 28 of the user's ear. When the cushion 106 deforms and conforms to the shape of the user's ear 10, a relatively large area of contact is formed between the cushion 106 and the concha region 18 of the ear 10. The resistance to the spring force by the concha 18 is, therefore, spread over a relatively large area and the actual pressure applied to the concha 18 at any one point is substantially reduced. This lower pressure results in greater comfort for the user.

The cushion 106 also serves as a noise barrier, preventing air leakage between the cushion 106, the concha 18, and the ear canal 30, and serves to dampen any noise that tends to penetrate the cushion 106. Where the cushion material is sufficiently soft and pliable, it will conform to the shape of the concha 18 and seal the entrance 28 to the ear canal 30, thus eliminating or, at least, substantially decreasing the leakage of air. If the cushion material has sufficient noise damping qualities, it will diminish the noise that may be transmitted through the cushion. The moldable putty discussed above particularly provides sufficient noise-damping qualities.

FIGS. 7, 8A and 8B illustrate the details of the IEC adapter 96. As mentioned above, the IEC adapter 96 has a tapered plug section 98 and an adapter section 100 with an inner chamber 94. The inner chamber 94 is contoured to substantially match the outer contours of the transducer housing 54 and the end cap 82. In particular, the chamber 94 is circular in cross-section and has a constant diameter (0.365 in. (.927 cm.)) over a substantial portion of its length from the open end 112 toward the inner end 114. Closer to the inner end 114, the chamber 94 has a segment of increased diameter (0.436 in. (1.107 cm.)) which defines a circular recess 116 for receiving a flange 118 formed on the end of the transducer housing 54. The remainder 120 of the chamber 94 tapers inward in conformity with the outer shape of the end cap 82. As shown in FIG. 8A, the outer surface 122 of the adapter section 100 tapers radially outward from the open end 112 to an area 124 where the adapter section 100 intersects with the plug section 98. The adapter section 100 is shown having a 0.688 in. (1.75 cm.) outermost diameter.

The outer surface 126 of the plug section 98 of the IEC adapter 96 tapers radially inward from the area 124 of intersection with the adapter section 100 to the open end 104. Preferably,

the taper has a slight convex curve as shown. The passageway 102 extends through the center of the plug section 98 and is circular in cross-section as shown.

Alternatively, the plug section 98 can be greater in length and smaller in diameter than shown so that it may protrude further into the ear canal 30. FIG. 7 illustrates in phantom an example of a plug section 98' of greater length and smaller diameter. The specific length and thickness of the plug section 98' may depend upon the size of the ear canal 30 and how far the user wishes to insert the plug section 98' into the ear canal 30. In general, a more comfortable and secure fit may be attained the further the plug section is inserted into the ear canal 30 (*e.g.*, in a mid-ear-canal area closer to the ear drum 32).

In the area 124 of intersection between the plug and adapter sections 98, 100, the IEC adapter 96 curves outwardly to form a forward-facing concave indent 128 to match the curvature of the torus-shaped cushion 106. In the embodiment shown in FIGS. 8A, 8B, the indent 128 has a radius of curvature of 0.065 in. (0.165 cm.). When positioned on the IEC adapter 96, the torus-shaped ear cushion 106 fits partially into the indent 128 as shown in FIG. 5. The radius of curvature of the end of the torus-shaped cushion 106, that is seated in the indent 128, is also approximately 0.065 in. (0.165 cm.).

The IEC adapter 96 may be made from an elastomer with a softness in the range of 50-55 Shore A Durometer. For an IEC adapter 96 having a longer and thinner plug section 98', the IEC adapter, however, may be made from a softer elastomer so that the plug section 98' can bend more easily as it is inserted into the user's ear canal 30.

As discussed further above, when the user inserts the plug section 98 (98') into the ear 10, the ear cushion 106 contacts the concha region 18 of the outer ear. The pressure from the ear-tube spring mechanism 52 causes the cushion 106 to substantially deform and assume the shape of the concha region 18. The area of contact between the cushion 106 and the concha region 18 is relatively large, resulting in the spring force being distributed over a relatively large area. This large distributed area of force further results in a much lower unit of pressure being applied to the flesh around the entrance to the ear canal. Preferably, the cushion 106 is made large enough to reduce or eliminate the amount of contact between the plug section 98 and the entrance 28 to the ear canal 30. In other words, the cushion 106 preferably is sized to receive and distribute to the concha region 18 of the ear 10 a substantial amount of the force being applied by the ear-tube spring mechanism 52.

The earpiece assembly 108 (*i.e.*, IEC adapter 96 and ear cushion 106) may also be adapted for use as a comfortable ear plug for blocking the entrance of noise into the user's ear canal 30. Preferably, the earpiece would have the longer and thinner plug section 98' shown in FIG. 7. The chamber 94 of the IEC adapter 96 may be filled with a sound absorbing material, or the adapter 96 can be formed into a solid piece.

5 With reference to FIG. 4, the details of the transducer housing 54 will be explained. In the embodiment shown, the transducer housing 54 is made from aluminum but may be made from other suitable materials such as engineering grade plastic. As mentioned above, the transducer housing 54 has first and second cylindrical inner chambers 64, 66, respectively. The housing 54 is symmetrical about the its longitudinal axis with its outer surface being circular in  
10 cross-section along its length. The outer surface further has a first segment 130 that is relatively short in length (0.037 in. (0.094 cm.)) and defines the flange 118. The diameter of the flange 118 is 0.436 in. (1.107 cm.). When the housing 54 is inserted into the IEC adapter chamber 94, the flange 118 is received into the chamber recess 116 so that the segment 130 is essentially press-locked in place.

15 The outer surface of the housing 54 further has a second segment 132 of smaller diameter (0.365 in.; 0.927 cm.) but greater length (0.704 in.; 1.788 cm.) than the first segment 130. The second segment 132 has a knurled surface which enables the walls of the IEC adapter chamber 94 to better grip the transducer housing 54. The knurled surface also provides a rough surface that enhances cement bonding if the IEC adapter 96 is bonded to the housing 54. As  
20 mentioned further above, however, the IEC adapter 96 may be merely press fit onto the transducer housing 54 so that the IEC adapter 96 may later be removed if desired; in which case, the knurled surface helps prevent sliding of the adapter 96 about the housing 54.

The outer surface of the housing 54 has a third segment 134 of greater diameter (0.436 in.; 1.107 cm.), equal to the diameter of the first or flange segment 130, and a relatively short  
25 length (0.094 in.; 0.239 cm.). The edge 136 of the third segment 134 forms a lip which engages the outer end 140 of the IEC adapter 96. Lastly, the outer surface of the housing 54 has a fourth segment 142 which tapers inward from the third segment 134. In the embodiment shown, the fourth segment 142 tapers at an angle of thirty degrees (30°).

30 FIGS. 9A, 9B, 10, and 11A-D illustrate the details of the components of the encapsulated transducer assembly 76. FIGS. 9A and 9B illustrate the details of the end cap 82.

The end cap 82 includes: a cylindrical portion 144 which fits into the circular passageway 102 of the IEC adapter 96; a tapered disk portion 146 which fits into the tapered portion 120 of the IEC adapter chamber 94; and a short rectangular portion 148 which fits into the rectangular channel 80 of the transducer adapter body 78 and receives the audio output 110 of the transducer 56. The through hole 84 passes through the center of the end cap 82. The central axis R of the rectangular portion 148, however, is slightly offset from the central axis X of the end cap 82. In particular, the central axis R of the rectangular portion 148 is offset downward 0.014 in. (0.0356 cm.) from the central axis X as shown in FIG. 9B (axis X is shown going into the page in FIG. 9B). Preferably, the end cap 82 is made from plastic but may be made from other suitable materials as well.

FIGS. 11A-11D illustrate the details of the transducer adapter body 78. The transducer adapter body 78 is cylindrical in shape with a rectangular hole 80 passing through its length. The adapter body 78 is made thicker on one side 150 so that the central axis H of the rectangular hole 80 is positioned slightly off center of the central axis Y of the transducer adapter body 78 as shown in FIG. 11C. The offset of the rectangular hole 80 is equal to the offset of the rectangular portion 148 of the end cap 82. As explained further below, the offsets help to properly align the transducer 56 so that the audio output 110 is aligned with the central axis X of the end cap 82. When the end cap 82 is positioned on the end of the transducer adapter body 78, the central axes X and Y are aligned, and the rectangular portion 148 and the rectangular hole 80 are aligned. Preferably, the transducer adapter body 78 is made from plastic or other material similar to the material of the end cap 82.

FIGS. 10 and 11A-11D illustrate the general positioning of the transducer 56 within the transducer adapter body 78. In the present embodiment, the transducer 56 is an electrodynamic type speaker. An example of such a transducer 56 is model number ECA-3132 electrodynamic speaker available from Knowles Electronics, Inc. of Itasca, Illinois. The transducer 56 is generally rectangular in shape and includes two contact points or mounts 88 to which the ends of the conductors 82 may be soldered. On the opposing end is the signal output port 110 which focuses the broadcast sound signal in the direction indicated by arrow S shown in FIGS. 11A and 11D.

The signal output port 110 is slightly offset upwardly from the central axis Z of the transducer 56 as shown in FIG. 11B (axis Z is shown into the page in FIG. 11B). Due to the

downward offset of the through hole 80 of the transducer adapter body 78, however, the signal output port 110 is aligned with the central axis Y of the transducer adapter body 78 when the transducer 56 is inserted into the through hole 80. When the IECR 42 is fully assembled, the signal output port 110 is received in the through hole 84 of the end cap 82 and is aligned with the central axis X of the end cap 82.

5           The through hole 80 of the transducer adapter body 78 may be filled with epoxy in order to fix the positioning of the transducer 56 within the through hole 80. By filling the through hole 80 with the epoxy, a short section 156 of the leads 86, adjacent the contact 88 and solder joint, will also be covered and afforded protection against external stresses that may be applied to the wire 86.

10           As described above, the two conductor wires or leads 86 are hard wired (*e.g.*, soldered) to the transducer 56. These leads 86 are very thin and are preferably twisted to form a rope-like construction. In order to protect the leads against undue torsional stresses, the leads 86 are preferably twisted in a direction so that the leads will have a tendency to unwind rather than twist further when the stethoscope tube 50 and transducer housing 54 are threaded together.

15           For example, the leads 86 would be carefully twisted in a counterclockwise direction where the end of the ear tube 50 is threaded in a clockwise direction. To further protect the wires 86 from torsional or other stresses, the wires 86 may be encased in a shielded cable that is fed through the ear-tube 50. In addition, as described above, the transducer 56 and a section 156 of the leads 86 adjacent the contacts 88 are encapsulated in the transducer adapter body 78 and surrounded by epoxy. The encapsulation of the section 156 of the wires 86 provides additional

20           protection against stress being applied to the wires 86 at the solder joints.

FIGS. 12A-C illustrate another embodiment of an encapsulated transducer assembly 160 that may be used in place of the encapsulated transducer assembly 76 shown in FIG. 10. FIGS. 12A-C in particular illustrate the assembly process for inserting the encapsulated transducer

25           assembly 160 into a modified transducer housing 54'. The transducer housing 54' is similar to the transducer housing 54 shown in FIG. 4 with the exception that the second chamber 66' and the passageway 90' have been modified as explained further below. In this embodiment, the transducer 56, rather than being encapsulated in the adapter body 78 and end cap 82, is encapsulated in a molded, solidified encapsulant or housing 162. An example of a suitable

30           material for encapsulating the transducer is an epoxy potting compound. Many well known

thermoplastic and thermosetting materials exist, however, that would be suitable for forming the solidified encapsulant 162.

In production, the pre-wired transducer 56 (*i.e.*, the transducer 56 with the twisted wires 86 or shielded cable attached thereto) is inserted into a mold and a plastic potting compound is poured or injected into the mold. The soldered wire terminals 164 and a short length 166 of the twisted wires 86 are also encapsulated in the potting compound in order to form a strain relief. By encapsulating the soldered joints 164 and a section 168 of the wires 86, any torsional displacement applied to the wires 86 external to the encapsulant 162 will not be transmitted to the wires 86 at the terminals 164 and, therefore, cannot cause any stress at the soldered joint 164. This stress relief is important as the wires 86 typically would be made from copper which can become embrittled after being subjected to heat. The copper wire immediately adjacent the terminal 164 would be particularly subjected to the heat of the molten solder and may become embrittled in an area known as the "heat affected zone". This embrittled, heat affected zone, would be more likely to break if subjected to undue stresses. By encapsulating a length 166 of the wires 86 that includes this zone, ample protection against breakage can be obtained.

The encapsulant or encapsulated housing 162 is molded so that its outer shape is generally symmetrical about its central longitudinal axis M. The shape is generally cylindrical with an outermost diameter slightly smaller than the inside diameter of the second chamber 66' of the transducer housing 54'. In addition the outer shape of the cylindrical encapsulant 162 at the solder terminal end 164 preferably tapers down to a diameter slightly larger than the diameter of the twisted wire bundle, *i.e.*, has a cone shape. The tip of the cone-shaped protuberant 168 is aligned with central longitudinal axis M resulting in the wires 86 extending slightly upward from the soldered joint 164 as shown in FIGS. 12A-C. The cone-shaped protuberant 168 may then mate with a corresponding concave cone shape 170 formed at the inner end of the second chamber 66' of the transducer housing 54'.

At the opposing end 172, a thin cylindrical tube 174 is placed about the audio output 110 of the transducer 56 and is also encapsulated in the potting compound. The tube 174 provides an audio passage 176 for sounds emitted from the transducer 56 and improves the structural integrity of the housing 162 near the audio end 172 so that the assembly may be safely fit into the IEC adapter 96. In addition, the outer shape of the end 172 is similar to the outer shape of the end cap 82 of the encapsulated assembly of FIG. 10 to further facilitate insertion of the



assembly into the adapter 96. As shown in FIGS. 12A-C, the tube 174 is aligned with the central longitudinal axis M of the encapsulated housing 162. In order to obtain the alignment, the encapsulated housing 162 is made thinner on the bottom as viewed in FIGS. 12A-C.

The outer surface of the cylindrical encapsulant 162 and/or the inner surface of the second chamber 66' of the transducer housing 54' may be lubricated to facilitate the assembly process. Thus, when the transducer housing 54' is threaded onto the ear tube terminal 58, the cylindrical encapsulant 162 is free to rotate, and the strain on the wires 86 is minimized. If the friction is too great and the encapsulant cylinder 162 resists rotation, the previously twisted wires 86 may tend to unwind (if wound in a direction opposite the direction of twisting of the transducer housing 54') or may be subjected to additional twisting forces (if wound in the same direction of twisting as the transducer housing 54'). The combination of the encapsulation of the transducer 56' as described above and the lubrication of the resulting encapsulant 162 results in a robust product that can sustain the rigors of rough handling. As the outer configuration of the transducer housing 54' is similar to the outer configuration of the transducer housing 54 shown in FIG. 4, the assembled transducer assembly 92' may be easily substituted for the transducer assembly 92 of the IECR 42.

FIGS. 13-15 illustrates another embodiment of an IECR 180 that has a contoured ear cushion 182 and IEC adapter 184. The IECR 180 comprises a modified encapsulated transducer assembly 160' (FIG. 15) that is similar to the encapsulated transducer assembly 160 shown in FIGS. 12A-C except where noted below. The encapsulated transducer assembly 160' includes a transducer 56 pre-wired with conductor leads 86. Positioned about the audio output 110 of the transducer 56 is a relatively long, thin cylindrical audio tube 174'. The transducer 56, audio tube 174' and a short length 166 of the conductor wires 86 are encapsulated in a solidified encapsulant or encapsulating housing 162' formed from a plastic potting compound in a manner described above with reference to FIGS. 12A-C.

The outer shape of the encapsulant 162' of FIGS. 13-15 is generally cylindrical and symmetrical about a central longitudinal axis N. The wired end of the encapsulant 162' tapers into a conical protuberant 168' much like the conical protuberant 168 of the encapsulant 162 of FIGS. 12A-C. The audio end 172' has been modified, however, so that the audio tube 174' extends beyond the encapsulated housing 162' and the encapsulated housing 162' tapers inward to the outer surface of the audio tube 174'.

The conical protuberant end 168' of the encapsulant 162' is fit into the second chamber 66" of a transducer housing 54". The transducer housing 54" is similar to the transducer housing 54' of FIGS. 12A-C having a second chamber 66' with a concave conical inner end 170'. The exterior of the end 186 of the transducer housing 54", however, has been slightly modified to provided an annular flange 188 which mates with a counter bore 190 provided in IEC adapter 184. As shown in FIGS. 13-15, the transducer housing 54" may be threaded onto the end of the stethoscope tube 50.

The fully assembled transducer assembly 92" (encapsulated transducer assembly 160' and transducer housing 54") may be press fit into the inner chamber 192 of the IEC adapter 184. The inner chamber 192 has a contour that corresponds to the outer contour of the transducer assembly 92". In particular, the inner chamber 192 has a cylindrical audio passage 194 for receiving the exposed section of the audio tube 174', a concave conical section 196 for receiving the audio conical end 172' of the encapsulant 162', an annular indent 198 for receiving the flange 118' of the transducer housing 54", a straight cylindrical section 200, and the counter bore 190. As explained more detail below, the exterior of the IEC adapter 184 has been modified to accommodate the contoured ear cushion 182.

With reference to FIGS. 16A-D, the ear cushion 182 has a generally "sea-shell" shape with a central through hole 202 and comprises a soft pliable material as described with reference to the cushion 106 of FIG. 3. As shown in FIGS. 16A and 16D, the cushion 182 has generally a sea-shell shape with a protruding notch 204 defined by two indented sections 206. The opposing side 208 of the cushion 182 has generally a semi-circular configuration as shown in FIGS. 16A and 16D. In addition, as shown in FIGS. 16B and 16C, the outer surface of the cushion 182 and the central through hole 202 taper inwardly toward the front end 210 of the cushion. As explained further below, when the IECR 180 is inserted into the user's ear 10, the semi-circular side 208 is pressed against the concha region 18, and the notch 204 is fit into the iscusua or notch 26 between the tragus 22 and antitragus 24 of the ear 10.

As mentioned above, the IEC adapter 184 has been configured to accommodate the contoured cushion 182. With reference to FIGS. 17A-17F, the IEC adapter 184 has a cushion-supporting section 212 and an adapter section 214. The cushion-supporting section 212 has a cylindrical audio segment 216 of reduced diameter, a tapered cushion-receiving segment 218, and a forward-facing, concave segment 220. As shown in FIG. 17B, the cushion-receiving

segment 218 and concave segment 220 both have generally a "sea-shell" configuration with a semi-circular side (218A, 220A) and a "notched" side (218B, 220B).

With reference to FIGS. 16A-D, the rear end 222 of the ear cushion 182 has a protruding section 224 on its semi-circular side 208 that is received in the semi-circular side 220A of the IEC adapter concave segment 220. The ear cushion 182 further has a protruding notch 226 that is received in the "notched" side 220B of the IEC adapter concave segment 220. The tapered through hole 202 of the cushion 182 is shown having a generally cylindrical configuration which, due to the cushion material, may be easily pressed about the cushion-receiving segment 218 of the IEC adapter 184 to conform with the shape of the cushion-receiving segment 218.

As shown in FIGS. 17A and 17D-F, the outer surface of the adapter section 214 of the IEC adapter 184 is contoured so that its cross-section progresses from a sea-shell configuration at the adapter section's forward end 230 to a circular configuration at its rear end 232. This configuration prevents the adapter section 214 from interfering with the user's ear 10 when the IECR 180 is inserted in the user's ear and provides a more finished appearance to the assembly 180.

With reference to FIG. 13, when the IECR 180 is inserted into the user's ear 10, the cushion 182 is pressed against the concha region 18 entrance 28 to the ear canal 30. The cushion 182 deforms to the shape of the surface of the ear and establishes a good seal about the entrance 28 to the ear canal 30. The large, semi-circular side 208 of the cushion 182 in particular fills the concha region 18, reducing the pressure applied to the concha 18 and entrance 28 to the ear canal 30 by the stethoscope spring mechanism 52. The cushion 182 also prevents or substantially reduces contact between the IEC adapter 184 and the concha 18 and entrance 18 to the ear canal, thus providing a more comfortable fit.

FIGS. 18-20 illustrate additional embodiments of IECRs 230, 240, and 250, respectively, that may be used with a more conventional, mechanical stethoscope that transmits audio signals from the stethoscope head to the earpiece via a column of air in the ear tube 50'. The outer configuration of each of the IECRs 230, 240, and 250 is similar to the outer configuration of the IECR 180 shown in FIG. 13. The interior configurations, however, have been modified as these IECRs 230, 240, and 250 do not house transducers.

With reference to FIG. 18, IECR 230 comprises an ear cushion 182, identical to the ear cushion 182 shown in FIGS. 13-15, and an IEC adapter 184 that is identical to the IEC adapter 184 shown in FIGS. 13-15. The IECR 230 further has a cylindrical mounting adapter 232 with flanges 234, 236 that respectively fit in the indent 198 and counterbore 190 of the IEC chamber 192. The mounting adapter 232 further has an audio segment 237 of greatly reduced diameter, which is received in the audio passage 194 of the IEC adapter 184.

The mounting adapter 232 also has a mounting chamber 238, similar in configuration to the second chamber 64 of the IECR 42 shown in FIG. 4, that allows the mounting adapter 232 to be threaded onto the end 58' of a mechanical stethoscope 50'. A thin audio passage 239 couples the mounting chamber 238 to an opening 235 at the forward end of the housing 232 and allows passage of the audio signal transmitted by the ear tube 50' through the adapter 232 and out the opening 235.

The IECR 240 of FIG. 19 is identical to the IECR of FIG. 19 except that the mounting chamber 238' of the mounting adapter 232' has been modified to accommodate a different terminal configuration for the end 58" of the stethoscope tube 50". The end 58" of the stethoscope tube 50" is provided with several annual ridges 242 that are press fit into corresponding annular indents 244 provided in the mounting chamber 238'.

The IECR 250 of FIG. 20 is similar to the IECR 240 of FIG. 19 except that the IECR 250 does not have an mounting adapter 232'. Rather, the interior chamber 192' of the IEC adapter 184' is shaped in a manner similar to the shape of the interior of the adapter housing 232' of the IECR 240 so that the IEC adapter 184' may directly receive the end 58" of the stethoscope tube. In particular, the chamber 192' of the IEC adapter 184' has a mounting chamber 254 that is identical to the mounting chamber 238' of FIG. 19 and an audio tube 256 identical to the audio tube 239 of FIG. 19.

It should be noted that the mounting chamber 254 of the IEC adapter 184' of FIG. 20 may alternatively be provided with mounting threads so that the adapter 184' may be threaded onto the end of a threaded stethoscope tube. Furthermore, the IECR 250 may be modified for use with an electronic stethoscope. In particular, the interior chamber 192' of the IEC adapter 184' may be modified to include a transducer chamber shaped to receive and hold an encapsulated transducer assembly (76, 160, or 160'). Such a modified IECR would not have a transducer housing (54, 54', or 54")

While several embodiments of the invention, including various modifications, have been shown and described, it should be recognized that other variations, substitutions, or modifications will occur to those skilled in the art. For example, the specific dimensions of the invention may vary from the examples described herein. Furthermore, different features from certain of the embodiments may be substituted for similar type features in other embodiments, *e.g.*, the mounting arrangement illustrated in FIG. 19 may be used for the other embodiments as well. Any such variations, substitutions, and modification are intended to fall within the scope of the invention.

## WHAT IS CLAIMED IS:

## 1. An earpiece comprising:

an ear plug having a first end and a second end insertable into the ear canal of a user's ear; and

5 concha cushion means mounted to said ear plug for contacting the concha region of a user's ear and preventing substantial contact of said ear plug with the concha region of the user's ear when said ear plug is inserted into a user's ear, said concha cushion means comprising a soft compressible material that is easily conformable to the surface of the user's ear.

## 10 2. An earpiece comprising:

an ear plug having a first end and a second end insertable into the ear canal of a user's ear, wherein said ear plug further has an ear canal section adjacent said second end, an outer ear section adjacent said first end, and a concha section disposed between said ear canal and outer ear sections, whereby said ear canal section is disposed in the ear canal of a user's ear, the  
15 concha section is disposed adjacent the concha region of the user's ear, and the outer ear section is disposed outside the user's ear when said second end of said ear plug is inserted into the user's ear canal; and

at least one concha cushion mounted to said concha section of said ear plug and comprising a compressible material such that said concha cushion contacts and conforms to the  
20 concha region of the user's ear when said second end of said ear plug is inserted into the user's ear canal.

3. The earpiece of claim 2, wherein said at least one concha cushion has generally a torus shape with a through hole and encircles said concha section of said ear plug.

25 4. The earpiece of claim 2, wherein said concha cushion has generally a fan-like configuration with a protruding notch on one side and an enlarged semi-circular portion on another side such that said protruding notch is disposed between the user's tragus and antitragus and the enlarged semi-circular portion is disposed in the user's concha when said earplug is inserted in the user's  
30 ear.

5. The earpiece of claim 2, wherein said concha cushion comprises a soft foam elastomer.

6. The earpiece of claim 2, wherein said concha cushion comprises a gelatinous material.

7. The earpiece of claim 2, wherein said concha cushion comprises a putty material.

8. The earpiece of claim 2, further comprising a transducer disposed in said ear plug.

9. The earpiece of claim 2, wherein said first end of said ear plug is provided with mounting means for coupling said ear plug to an audio device.

10. The earpiece of claim 2, further comprising:

a transducer housing disposed in said ear plug, said transducer housing having a chamber; and

a transducer disposed in said transducer housing.

11. A stethoscope comprising:

a stethoscope head;

at least one sound transmission tube coupled to said stethoscope head; and

at least one earpiece mounted to said at least one sound transmission tube, said earpiece comprising:

an ear plug having an inner chamber and a protruding section insertable into the ear canal of a user's ear; and

a transducer assembly removably positioned in said inner chamber of said ear plug, said transducer assembly comprising a transducer housing and a transducer positioned in said transducer housing.

12. The stethoscope of claim 11, wherein said earpiece further comprises a concha cushion positioned on said ear plug.

13. An in-ear-canal audio receiver comprising:

an in-ear-canal adapter body having a protruding, tapered, ear plug portion, an opening in the plug portion, an exterior annular indent, and an inner chamber coupled to the opening of the plug portion;

a transducer assembly positioned in said inner chamber of said in-ear-canal adapter body, said transducer assembly comprising a transducer housing having a through passage and a  
5 transducer positioned in said passage; and

a cushion positioned in the annular indent of the in-ear-canal adapter body.



14. The in-ear-canal audio receiver of claim 13, wherein said transducer housing comprises a transducer adapter body having a through hole and an end cap which covers one end of said  
10 through hole of said transducer adapter body, wherein said transducer fits into the through hole of the transducer adapter body.

15. The in-ear-canal audio receiver of claim 13, wherein said transducer housing comprises an epoxy material that surrounds said transducer.

16. The in-ear-canal audio receiver of claim 13, wherein said transducer assembly further comprises a transducer adapter body having a through hole and an end cap which covers one  
15 end of said through hole of said transducer adapter body, wherein said transducer fits into the through hole of the transducer adapter body, and said transducer adapter body together with  
20 said transducer are received in said passage of said transducer housing.


17. The in-ear-canal audio receiver of claim 13, wherein said transducer assembly further comprises an encapsulating housing that surrounds said transducer, said encapsulating housing  
25 comprising an epoxy material and being received in said passage of said transducer housing.






**THIS PAGE BLANK (USPTO)**

FIG. 3



**THIS PAGE BLANK (USPTO)**



**THIS PAGE BLANK (USPTO)**

FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C



FIG. 7




FIG. 8A







FIG. 8B






**THIS PAGE BLANK (USPTO)**






**THIS PAGE BLANK (CONT.)**




**THIS PAGE BLANK (CONT.)**

FIG. 13



**THIS PAGE BLANK (USP 10,**


FIG. 14



**THIS PAGE BLANK (USPTO)**



FIG. 15



**THIS PAGE BLANK (CONT.)**

FIG. 16B




FIG. 16D




FIG. 16A













FIG. 16C




**THIS PAGE BLANK (USPTO)**




**THIS PAGE BLANK (USE)**

FIG. 18




**THIS PAGE BLANK (USPTO)**





**THIS PAGE BLANK (CONT.)**

FIG. 20



**THIS PAGE BLANK (USPTO)**

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US97/02630

**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(6) : A61B 7/04

US CL : 381/67, 68.6; 181/130, 131, 135

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 381/67, 68.6; 181/130, 131, 135

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
NONE**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,208,867 A (STITES, III) 04 May 1993, Figure 5.	1,2,4,9
X	US 5,319,163 A (SCOTT) 07 June 1994, Figures 1-3.	1-4, 8-10, 13, 14
Y		----- 5-7, 15-17
X	US 4,048,444 A (GIAMPAPA) 13 September 1977, Figures 1, 2B, and 2C.	11,12

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (so specified)	*Z*	document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means		
*P* document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

20 MAY 1997

Date of mailing of the international search report

09 JUL 1997

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

F. W. Isen

Telephone No. (703) 305-4386

**THIS PAGE BLANK (USPTO)**